
Product data sheet


LIGHT LINEAR PT 2 BOLLARDS
LI-10032-T2-8027
LIGMAN



IP 65 IK 10


- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing - Extruded aluminium column - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	51 W	CRI	80
Total flux	5482 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	51 W

Light output 2 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	51 W	CRI	80
Total flux	5482 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	51 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 22.83 in
Width: 7.87 in
Height: 39.37 in
Weight: 14.9 kg

Adjustability

Fixed

Electric

System power: 102 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 10
Surface temperature: 40°C