Product data sheet


COLUMN LUMINAIRE RESIDENZA-2 C ZERO ASY34 16LED 2700K
88.00900.0V0XX + 99.20944.1V00X
HESS



IP 65


Illuminating column made of aluminium, consisting of top element and base element. Protective cover and luminaire glass made of clear PC glass. Light source sits on four aluminium rods. Cylindrical luminaire body made of cast aluminium. Diameter 200 mm. ULOR of 0%, complies with the Dark Sky Standard. Rods and internal parts uniformly painted, dark anthracite textured (similar to DB 703/Gris 2900 sablé). Total height of columns including luminaire 4600 mm

Light output 1




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2786 lm	Total flux	2786 lm
Luminous efficacy	112 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2519 lm	Total flux	2519 lm
Luminous efficacy	112 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2248 lm	Total flux	2248 lm
Luminous efficacy	111 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1970 lm	Total flux	1970 lm
Luminous efficacy	109 lm/W	Total power	18 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1683 lm	Total flux	1683 lm
Luminous efficacy	107 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1390 lm	Total flux	1390 lm
Luminous efficacy	104 lm/W	Total power	13.4 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1087 lm	Total flux	1087 lm
Luminous efficacy	98 lm/W	Total power	11.1 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3555 lm	Total flux	3555 lm
Luminous efficacy	112 lm/W	Total power	31.6 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3048 lm	Total flux	3048 lm
Luminous efficacy	112 lm/W	Total power	27.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3304 lm	Total flux	3304 lm
Luminous efficacy	112 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3803 lm	Total flux	3803 lm
Luminous efficacy	112 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 10.76 in
Width: 10.76 in
Height: 183.38 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65