


# Product data sheet

MINI RETINA-3  
7013-0-5-801-XX  
UNILAMP



Description RETINA is a round wall/ceiling light with robust aluminium construction and impact resistant polycarbonate lens cover. It utilizes a high quality mid-power SMD LED module. RETINA is also available with built-in microwave sensor and hi-low light function. The high protection rating of IP65 and IK09 allows RETINA to be installed in most outdoor environments. With a diffused light distribution, it provides general lighting in private and public areas and is perfect for commercial use. The front cover is available in various designs; moreover, RETINA is available in 2 sizes with the choice of 5 different colours. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. Replaceable for future upgrade. • Optional with motion detector (Microwave Sensor). • Quick connector for easy installation. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x LED			
Nominal lamp power	11 W	LOR	53%
Lamp flux	1130 lm	Total flux	603 lm
Luminous efficacy	103 lm/W	Total power	12 W
CCT	3000 K		
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 10.32 in  
Width: 4.72 in  
Height: 10.32 in

## Adjustability

Fixed

## Electric

System power: 12 W  
Controller: DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 09