

# Product data sheet

PLEIAD G4 125 BLACK WIDE REC HL 940  
73257  
FAGERHULT



Installation Recessed mounting in unventilated or ventilated suspended ceilings. Separate driver and installation clip for easy and tool-free installation supplied as standard. An assembly plate must be used when mounting on soft tile ceilings, see accessories. For detailed information, see the installation instructions. Connection Connection in separate driver box. Snap-in terminal block 3x1.5 mm<sup>2</sup> (x2), onward connection possible. 5x1.5 mm<sup>2</sup> (x2) when dimming. Can also be supplied with chassis mounted snap-in connector in the ballast where a T-splitter or mains cable and plug are possible. The luminaire body and driver are interconnected with a snap-in connector. Design Luminaire body in cast aluminium. Visible reflector ring in white aluminium (RAL 9003). Reflector Reflector of matt metallised aluminium, white (RAL 9003) or black (RAL 9005) finish. Reflector ring in white aluminium (RAL 9003). Lens of clear acrylic. Miscellaneous The luminaire is supplied with dust protection over the light opening. IP 64 under a suspended ceiling, IP 20 above a suspended ceiling.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	90
Total flux	1869 lm	LOR	100%
Luminous efficacy	89 lm/W	Total power	21 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 5.63 in  
Width: 5.63 in  
Height: 3.86 in

## Adjustability

Fixed

## Design

Color of housing: Black, White

## Electric

System power: 21 W

## Protection

IP: 64