Product data sheet

OUTDOOR LIGHTING

V1-S1-00760-40L30-6610050 LEVANTE URBAN 99W 5000K

VARTON

IP 66 IK 03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: streets and roads. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-urban-dlya-goroda/svetodiodnyy-svetilnik-varton-ulichnyy-levante-m-urban-100-vt-kronshteyn-60-mm-5000-k-ral9003-belyy-_2/

Light output 1



1 x LED

Nominal lamp power	99 W	LOR	100%
Lamp flux	13500 lm	Total flux	13500 lm
Luminous efficacy	136 lm/W	Total power	99 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 34.45 in

Width: 5.87 in

Height: 4.37 in

Adjustability

Fixed

Electric

System power: 99 W

Protection

IP: 66

IK: 03