

Product data sheet

ARCHITECTURAL LIGHTING
V1-G1-72335-21N01-6603040 REGULA 2.0 1500MM FOR CONTINUOUS LINES 30W 4000K LOW-VOLTAGE 15°
VARTON




IP
66

IK
07

Architectural linear wallwasher for continuous lines Flicker, %: 5 Length, mm: 1 452 Protection class: III Ingress protection (IP): IP66 Impact resistance: IK07 Power factor: 0,95 https://www.varton.ru/products/arkhitekturnoe-osveshchenie/regula-2-0/regula-2-0-1500mm-dlya-sborki-v-liniyu/svetodiodnyy-svetilnik-varton-arkhitekturnyy-regula-2-0-1500-mm-30-vt-4000-k-15-gradusov-dc24v-dlya-_1/

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	2850 lm	Total flux	2850 lm
Luminous efficacy	95 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.17 in
Width: 1.89 in
Height: 2.17 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 66
IK: 07