


Product data sheet

SUPER E1 1/4W LED830 700MA SP SRE
60814344
ZUMTOBEL



Recessed luminaire unit with 1 LED spotlight head; lamp(s): 1/4 W LED830, warm white; with spot beam pattern; Colour rendering Ra > 80, colour temperature 3000 K; Luminaire luminous flux: 227 lm, Luminaire efficacy: 57 lm/W; service life: 50,000h at 70% luminous flux; UV-free and IR-free light; compact design with minimalist look; LED spotlight unit can pivot through 360°, tilt through 90° and is retractable; spotlight can be fixed precisely in position; 2-piece LED spotlight unit made of milled aluminium in silver anodised finish; front cylinder of lamp unit accommodates interchangeable lens; recessed housing made of silver anodised aluminium; easy to fit without tools using spring clips in ceilings of thickness 1-26mm; ceiling cut-out: Ø40mm, recess depth: 60 mm; weight: 0.08 kg; Please note: please order control gear separately (700mA); please order just one power lead (60700226) for each control gear unit; if using the 3/6-way Multiplug sockets, please order one extension lead (60700225) for each luminaire unit.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	80
Total flux	227 lm	LOR	100%
Luminous efficacy	57 lm/W	Total power	4 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.43 in
Diameter: 1.85 in
Weight: 0.084 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 4 W
Appliance Class: III

Protection

Designation labels: CE