


Product data sheet

TX-MOVE
901739.004.1.76
RZB




Series: TX-MOVE Einlege/Einbau-Flächenstrahler. Housing: aluminium, powder-coated. 2xSwivel range: 90°. High-efficiency LED units with flush-mounted opal diffuser made of non-yellowing PMMA. Symmetrical wide beam light emission. Suitable for laying in grid ceiling module 625. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux variable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Replaceable components make repairs possible and extend the service life. Zwei DALI-Betriebsgeräte für zwei separate DALI-Adressierungen. Colour: silver, matt (approx. RAL 9006) Length: 622 mm Width: 190 mm Height: 39 mm Cut-out length: 602 mm Cut-out width: 174 mm Recess height: 100 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 35 W Rated luminous flux: 4900 lm Beam angle Down: 112° Luminous efficiency: 140 lm/W System power 2: 47 W Rated luminous flux 2: 6450 lm Luminous efficiency 2: 137 lm/W System power 3: 68 W Rated luminous flux 3: 8750 lm Luminous efficiency 3: 129 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20


Light output 1



1 x LED			
Nominal lamp power	17.5 W	LOR	100%
Lamp flux	2450 lm	ULOR	13%
Luminous efficacy	140 lm/W	Total flux	2450 lm
CCT	4000 K	Total power	17.5 W
CRI	80		



1 x LED			
Nominal lamp power	23.5 W	LOR	100%
Lamp flux	3225 lm	ULOR	13%
Luminous efficacy	137 lm/W	Total flux	3225 lm
CCT	4000 K	Total power	23.5 W
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

34 W
4375 lm
129 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
4375 lm
34 W


Light output 2**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

34 W
4375 lm
129 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
4375 lm
34 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

23.5 W
3225 lm
137 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
3225 lm
23.5 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

17.5 W
2450 lm
140 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
2450 lm
17.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.48 in
Width: 24.49 in
Height: 1.54 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Silver gray

Electric

System power: 35-68 W

Protection

IP: 20
IK: 03