

Product data sheet

MICRORING COMFORT

S.7900N.19


SIMES



Version is available on request. INGROUND DRIVEOVER MICRORING COMFORT S.7900N 1 module LED 4000K 220-240Vac ON-OFF Rated module luminous flux:: 320lm Rated luminaire luminous flux: : 197lm Rated module power: : 2.2W Rated luminaire power: : 3.65W Luminaire efficacy: : 54lm/W Voltage (AC): : 220-240Vac Frequency (AC): : 50/60Hz Voltage (DC): : 176-264Vdc Dimmable: : NOT DIMMABLE (ON-OFF) Electrical insulation class: : I Protection class IP: : IP65 IP67 Mechanical resistance: : IK10 CE SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at 700mA $V_{fmin}=2.6Vdc$ $V_{fmax}=3.1Vdc$. Example SIMES compatible power supplies (check the complete list of the drivers on the catalogue): Art. S.2438 POWER SUPPLY 230V/250mA-700mA 20W o 230Vac/24Vdc 16W 240Hz DALI DIMMABLE IN BOX IP67 Art. S.3426 POWER SUPPLY DALI MULTI-POWER 230V/250mA-700mA o 230V/24V 16W 240Hz IP20 NB: Use 1 Power Supply for each Luminaires LUMINAIRE TYPE Inground drive over fitting. Recessing depth 175 mm. IP rating IP 65 IP67 MATERIAL CHARACTERISTICS "Copper Free" Aluminium die cast housing in EN AB-44100 with high resistance against corrosion. Stone wash surface treatment prior to painting process. 3 mm thick front trim in Stainless Steel - Grade AISI 316L with 2,5-3% molybdenum content. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Pre treated Silicone Gaskets. Painting Process : 3 Step Process 1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 10 Maximum load capacity 5000 Kg LIGHTING PERFORMANCE Sophisticated optical systems able to considerably reduce glare thanks to the retracted position of the LED. The lathed anodized reflector is composed of HI-GRADE 99,98% pure anodized aluminium with a bright polish finish (Version with COB). transparent Toughened glass 12mm thick (10mm Microflat). Lamp adjustable $\pm 15^\circ$ position. LOR – Compact electronic ballast to guarantee better lamp stability, lifetime and reduced energy consumption. LOW SURFACE TEMPERATURE Surface temperature of glass $30^\circ C$ (T_a $25^\circ C$) Electronic Ballast generating less heat. Specific layout of internal components allow for better heat dissipation therefore limiting the temperature generated inside the fitting. RECESSING BOX Recessing box in Polypropylene with cable entry on all 4 sides also allows: 1) Easy wiring; 2) Cable management for fast connector; 3) Easy access to the fitting for maintenance purposes. WIRING Supply 0.5m cable section type H07RNF secured by cable gland PG 13.5 (\varnothing 6÷12 mm) and sealed with B component epoxy resin, wired internally protected by silicon sheaths. Fast connector M20 (\varnothing 5÷14 mm) supplied as standard for single cable connection . Connector housed inside the recessing box . Front re-lamping without removing the complete fitting . Isolation: CLASS I . Available colours: Stainless steel (cod.19). Weight: 1.77 Kg Glow Wire test: $750^\circ C$ LED module included This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user. This product contains a light source of energy efficiency class: E. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 T_a $25^\circ C$ (50,000 hours referable to L80 B10 T_a $40^\circ C$). Lifespan of the luminaire min. 50,000 hours at $40^\circ C$. Performance Ambient temperature T_q $25^\circ C$. Operating ambient temperature range is from $-20^\circ C$ to $+50^\circ C$. Storage temperature range from $-20^\circ C$ to $+60^\circ C$. ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE. We recommend installing surge protection devices ?SPD? in the electrical system. Protection devices prevent the intensity of these phenomena?s, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer

and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	3.65 W	CRI	90
Total flux	197 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	3.65 W

Mounting mode

Floor recessed

Shape and measurements

Height: 0.16 in
Diameter: 4.17 in

Adjustability

Tiltable

Design

Material impression: Glass, Stainless steel
Designer: SIMES S.P.A.

Electric

System power: 3.65 W
Appliance Class: I

Protection

IP: 67
IK: 10
Max. point load: 5000 kg
Designation labels: CE