

# Product data sheet

## LIGHTALK 7 WALL WASHER FLOODLIGHTS


LA-30014-E-40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40,65 - Die-cast aluminium end-caps, extruded aluminium housing and aluminium front frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear for LA-30001, LA-30002, LA-30013, LA-30014 - Remote driver is included for LA-30021, LA-30022

### Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	18.5 W	CRI	80
Total flux	1472 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	100%
		Total power	18.5 W

### Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	18.74 W	CRI	-50
Total flux	187 lm	LOR	100%
Luminous efficacy	10 lm/W	ULOR	100%
		Total power	18.74 W

### Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	18.7 W	CRI	-18
Total flux	1119 lm	LOR	100%
Luminous efficacy	60 lm/W	ULOR	100%
		Total power	18.7 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	14.2 W	CRI	-29
Total flux	825 lm	LOR	100%
Luminous efficacy	58 lm/W	ULOR	100%
		Total power	14.2 W

Mounting mode

Wall mounted, Floor mounted

Shape and measurements

Length: 3.54 in  
Width: 47.24 in  
Height: 2.56 in  
Weight: 5.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 70.15 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

Protection

IP: 67  
IK: 10  
Surface temperature: 40°C