Product data sheet

LUCAS III (1-ARMED) 9.853.3066.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 k
CRI	54

LOR		84%
Total flu:	X	5697 lm
Total po	wer	137 W



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR		
Lamp flux	4000 lm	Total flux		
Luminous efficacy	38 lm/W	Total power		
CCT	3400 K			
CRI	54			

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 89-137 W

Protection

IP: 55

84% 3351 lm 89 W