# Product data sheet


SINUS CURVED SEGMENT DI/ID SILVER PRISM. 90° R730
P33-H39-9006E2930L1M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 3000K CRI 90 29,5W 3377lm[1] [1]Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 13,2% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 7.38 W | CRI | 90 |
| Total flux | 844 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | Total power | 7.38 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 7.38 W | CRI | 90 |
| Total flux | 844 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | Total power | 7.38 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 7.38 W | CRI | 90 |
| Total flux | 844 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | Total power | 7.38 W |

## Light output 4 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 7.38 W | CRI | 90 |
| Total flux | 844 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | Total power | 7.38 W |

### Mounting mode

Pendant, Contact rail

### Shape and measurements

Length: 30.12 in
Width: 30.12 in
Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 29.5 W

### Protection

IP: 40