


# Product data sheet

PURE 1  
09.1610/HI-PAR/20W/12°25°40°  
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.


## Light output 1



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1085 lm	LOR	100%
Luminous efficacy	54 lm/W	Total flux	1084 lm
CCT	3000 K	Total power	20 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1080 lm	LOR	100%
Luminous efficacy	54 lm/W	ULOR	100%
CCT	3000 K	Total flux	1079 lm
CRI	84	Total power	20 W



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1114 lm	LOR	100%
Luminous efficacy	50 lm/W	Total flux	1111 lm
CCT	3000 K	Total power	22 W
CRI	84		

## Mounting mode

Ceiling recessed

## Electric

System power: 20-22 W  
Appliance Class: II

#### Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.51 in

#### Adjustability

Rotatable, Tilttable

#### Protection

IP: 20