




Product data sheet

VEO Ø210MM
90-A037-14-00
LEDSC4



LedsC4 Veo ø210mm 90-A037-14-00V1 Downlight Structure material: Aluminium, Polycarbonate. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Semitransparent. Warranty: 5 Years. Product net weight (Kg): 0.6 Product length (mm): 230 Product width or diameter (mm): 230 Product height (mm): 100 Product aperture (mm): 3.2 Ø of the hole for recessing (mm): 200-220 Permitted ceiling thickness: 0-25 Class 2. Luminaire not suitable for coating with insulation materials. IP: IP54. LED. No. of lampholders or LEDs: 1. LED brand: VOSSLOH. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 17.5W. Colour temperature: 4000K. Colour rendering index: 82. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 19.8. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 2751. Real lm/W: 144. Voltage / frequency range: 220-240V, 50/60Hz. Voltage: 36. Equipment included: Yes. Total power: 19.1. Power factor: 0.97. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	19.1 W	LOR	100%
Lamp flux	2751 lm	Total flux	2751 lm
Luminous efficacy	144 lm/W	Total power	19.1 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.06 in

Width: 9.06 in

Height: 0.12 in

Adjustability

Fixed

Electric

System power: 19.1 W

Appliance Class: II

Protection

IP: 54