

# Product data sheet


LED MINI PANEL RPE SERIES 18W 3000/4000/6500K  
RPE-18/3C  
MPE



IP  
20

- Round shape - Recessed - mounted on ceiling or use additional SRPE accessories for floating mounting - Light guide plate made of PMMA plastic for uniform light distribution - Driver is integrated inside the light. - The light has 3 color modes: Warm White-Cool White-Natural - Size: Ø223 x 25 mm - Cut out: Ø203mm - Voltage: 110-265VAC - Power: 18W - Power Factor (PF): >0.5 - Luminance: 1500 lm - Color Temperature (CCT):2800-3200K/6000-6500K/4000-4500K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

## Light output 1



1 x LED Module			
Nominal lamp power	18 W	LOR	100%
Lamp flux	4500 lm	Total flux	4500 lm
Luminous efficacy	250 lm/W	Total power	18 W
CCT			
CRI	82		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 9.58 in  
Width: 8.78 in  
Height: 0.98 in

## Adjustability

Fixed

## Electric

System power: 18 W

## Protection

IP: 20