

Product data sheet

LED MINI PANEL RPE SERIES 18W 3000/4000/6500K

RPE-18/3C


MPE



IP
20

- Round shape - Recessed - mounted on ceiling or use additional SRPE accessories for floating mounting - Light guide plate made of PMMA plastic for uniform light distribution - Driver is integrated inside the light. - The light has 3 color modes: Warm White-Cool White-Natural - Size: Ø223 x 25 mm - Cut out: Ø203mm - Voltage: 110-265VAC - Power: 18W - Power Factor (PF): >0.5 - Luminance: 1500 lm - Color Temperature (CCT):2800-3200K/6000-6500K/4000-4500K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

Light output 1



1 x LED Module

| | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 18 W | LOR | 100% |
| Lamp flux | 4500 lm | Total flux | 4500 lm |
| Luminous efficacy | 250 lm/W | Total power | 18 W |
| CCT | | | |
| CRI | 82 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.58 in

Width: 8.78 in

Height: 0.98 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 20