Product data sheet

LINEAR LIGHTING

V1-R0-1S828-02OP0-4004030 X-LINE SQUARE 0,5 X 0,5 M 40W 3000K


VARTON



IP 40 IK 01

• Extruded aluminum rectangular luminaire Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,9 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-figury/x-line-kvadrat-0-5-kh-0-5-m/cvetilnik-varton-kh-line-kvadrat-40-vt-podvesnoy-3000-k-575x575x100-mm-ral9003-belyy-muar-s-rasseiva/

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	100%
Lamp flux	4200 lm	Total flux	4201 lm
Luminous efficacy	105 lm/W	Total power	40 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 22.64 in

Width: 22.64 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 40

IK: 01