

Product data sheet


RLB8-40LH-FAM-EDU
CURRENT



IP
48

The Reverie RLB is a decorative low bay for Educational, automotive and retail spaces. Distribution options and multiple control capabilities for customization. Uninterrupted ribbon of light for single or row mount applications, Six LED color choices available in 80 and 90 CRI, Available in 4' and 8', Optional integral emergency battery pack, Heavy gauge steel housing, die embossed for maximum rigidity, Injection molded ABS material endcaps, LED boards and driver accessible for future maintenance or upgrades, Modular replaceability of LED components, Surface mount, stem mount or cable mount, Long life 60,000 hour LEDs at L80 for reduced maintenance, Optional SpectraSync™ offers three modes of tunable white solutions and integrates seamlessly into a variety of control systems, NX Lighting Controls provides options for standalone and networked integrated sensor with wired or wireless connectivity for NX system deployments, Five year warranty,

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	126.6 W	CRI	80
Total flux	15517 lm	LOR	100%
Luminous efficacy	123 lm/W	ULOR	8%
		Total power	126.6 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 8.03 in
Width: 95.98 in
Height: 2.99 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 126.6 W

Protection

IP: 48