


# Product data sheet

SAFESITE LED AREA LIGHT 5700 LUMENS, 360° DISTRIBUTION, TEMPERED GLASS LENS  
ALD7BC26-XXXXX-N  
DIALIGHT



SafeSite LED Area Light 5,700 Lumens 40 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Tempered Glass Lens Class I Div 2 Groups A,B,C,D Class III Div 1&2 UL 844 UL 1598/A CSA C22.2 No. 137-M81 NEMA 4X Factory Sealed IK07 360° Distribution IP66/67/69 Scaled IES File

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 5181 K |
| Nominal lamp power | 40 W     | CRI         | 80     |
| Total flux         | 5700 lm  | LOR         | 100%   |
| Luminous efficacy  | 142 lm/W | Total power | 40 W   |

## Mounting mode

Pendant

## Shape and measurements

Length: 10.70 in  
Width: 9.70 in  
Height: 5.70 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 40 W  
Voltage: 100 V AC, 277 V AC, 120 V DC, 250 V DC  
Appliance Class: I

## Protection

IP: 66  
IK: 07