

# Product data sheet

CIRCLED SINGLE GREY 30W LED 4000K RA>80


8246084507

SG ARMATUREN



Design: Christian Hvidt Light for mounting on mast, IP65-rated. Luminaire body made of die-cast aluminium, powder-coated in black or grey. Reflector made of aluminium, powder-coated white. Optics are particularly well suited to giving a direct light distribution due to the tempered glass front. Complete with LED driver for operation of LED light sources mounted to component rail pre-mounted with six-metre connection cable. Lamp head prepared for mounting at 60 mm. Electrical rating class II. IK09. CircLED is based on the latest LED technology and optics for a long-lasting solution for streets and small roads, public areas and paths. CircLED is available as a single lens or a multi-lens version. Both combine energy savings, durability and precise light distribution and are optimal solutions for retrofitting of old mercury or sodium lamps. Light distribution: Direct Asymmetric (Single Lens) Light technic LED 30W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class II IP66 IK09 Energy and approvals A++ CE Materials and finish Housing: Die-cast aluminium Colour: Grey (structure 2150 sablé) Optics: Glass Mounting/Connection Post - top (Ø60mm), Outdoor Cable 2x1mm<sup>2</sup> 6m Wind projected area: 415cm<sup>2</sup> - Max 8 kg Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 30 W     | CRI         | 80     |
| Total flux         | 3320 lm  | LOR         | 100%   |
| Luminous efficacy  | 111 lm/W | Total power | 30 W   |

## Mounting mode

Standing / Bollard, Pole top mounted

## Shape and measurements

Length: 18.10 in

Width: 15.37 in

Height: 8.18 in

## Adjustability

Fixed

## Electric

System power: 30 W

Appliance Class: II

## Protection

IP: 66

IK: 09