Product data sheet


DEECOS S MICRO
742153.003.2
RZB



IP 20 IK 06

Series: DEECOS S micro LED surface-mounted projector in modern design with no visible cooling ribs. Housing made of die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With multi adapter for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: deep black, matt (RAL 9005) Diameter: 60 mm Height: 110 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 System power: 16 W Rated luminous flux: 1950 lm Beam angle Down: 38° Luminous efficiency: 122 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	16 W	CRI	90
Total flux	1950 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	13%
		Total power	16 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.33 in
Diameter: 2.36 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 16 W

Protection

IP: 20
IK: 06