Product data sheet


TRIONA RECTANGLE A
312714.002.1.730
RZB



IP 20 IK 03

Series: TRIONA rectangle Decorative rectangular LED surface-mounted luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Direct light emission through a diffuser made of non-yellowing plastic (PMMA) opal.Indirect light emission through a flush diffuser made of satin-finish plastic. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Direct 70%, indirect 30% light emission. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug-and-play connector system. Driver integrated. With Casambi smart+free Bluetooth control for wireless network and operation using Android / iOS devices, free app available for download. Direct/indirect light emission can be switched and controlled separately. Suitable for through-wiring. Colour: traffic white, matt (RAL 9016) Length: 1560 mm Width: 350 mm Height: 88 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 144 W Rated luminous flux: 18000 lm Beam angle Down: 108° / 107° Luminous efficiency: 125 lm/W Control gear: Dimmable Bluetooth converter Control gear: Konverter dimmbar Bluetooth Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	144 W	CRI	80
Total flux	18000 lm	LOR	67%
Luminous efficacy	125 lm/W	ULOR	14%
		Total power	144 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.78 in
Width: 61.42 in
Height: 3.46 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 144 W

Protection

IP: 20
IK: 03