


# Product data sheet

CLARA VII (OPAL ATTACHMENT)  
9.767.1052.00  
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination -Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately

## Light output 1



|                       |          |             |         |
|-----------------------|----------|-------------|---------|
| 1 x Metal halide lamp |          |             |         |
| Nominal lamp power    | 100 W    | LOR         | 58%     |
| Lamp flux             | 10000 lm | ULOR        | 13%     |
| Luminous efficacy     | 50 lm/W  | Total flux  | 5762 lm |
| CCT                   | 3000 K   | Total power | 115 W   |
| CRI                   | 90       |             |         |

## Mounting mode

Pole top mounted

## Electric

System power: 115 W

## Shape and measurements

Height: 27.56 in  
Diameter: 29.92 in