Product data sheet

PRO-STRADA MINI, 12LEDS OPTIEK 1
41360X0X
PROLUMIA



IP 66 IK 08

Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1



1 x LED

Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1400 lm	ULOR	9%
Luminous efficacy	131 lm/W	Total flux	1400 lm
CCT	4000 K	Total power	10.7 W
CRI	80		



1 x LED

Nominal lamp power	15.3 W	LOR	100%
Lamp flux	2000 lm	ULOR	9%
Luminous efficacy	131 lm/W	Total flux	2000 lm
CCT	4000 K	Total power	15.3 W
CRI	80		



1 x LED

Nominal lamp power	16.2 W	LOR	100%
Lamp flux	2000 lm	ULOR	9%
Luminous efficacy	123 lm/W	Total flux	2000 lm
CCT	3000 K	Total power	16.2 W
CRI	80		



1 x LED

Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1800 lm	ULOR	9%
Luminous efficacy	130 lm/W	Total flux	1800 lm
CCT	4000 K	Total power	13.8 W
CRI	80		



1 x LED

Nominal lamp power	14.6 W	LOR	100%
Lamp flux	1800 lm	ULOR	9%
Luminous efficacy	123 lm/W	Total flux	1800 lm
CCT	3000 K	Total power	14.6 W
CRI	80		



1 x LED

Nominal lamp power	12.3 W	LOR	100%
Lamp flux	1600 lm	ULOR	9%
Luminous efficacy	130 lm/W	Total flux	1600 lm
CCT	4000 K	Total power	12.3 W
CRI	80		



1 x LED

Nominal lamp power	11.3 W	LOR	100%
Lamp flux	1400 lm	ULOR	9%
Luminous efficacy	124 lm/W	Total flux	1400 lm
CCT	3000 K	Total power	11.3 W
CRI	80		



1 x LED

Nominal lamp power	13 W	LOR	100%
Lamp flux	1600 lm	ULOR	9%
Luminous efficacy	123 lm/W	Total flux	1600 lm
CCT	3000 K	Total power	13 W
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 22.87 in

Width: 12.09 in

Height: 4.25 in

Electric

System power: 10.7-16.2 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC