# Product data sheet


HCM1-2-3-4 MULTIPLES SERIES
HCMR2R25930ED010MW
COOPER LIGHTING



IP 47

1, 2, 3, or 4 inch multi-head recessed luminaires, Flange trim standard, rimless mud-in field installation kit available, Matte White and Matte Black finish options, 90 CRI; 2700K, 3000K, 3500K, 4000K CCT, Each multi-head delivers greater than 1200 lumens (nominal), Narrow Flood optic pre-installed; Spot & Flood optional accessories, Multi-heads rotate 355˚ and tilt 0-70˚ from nadir, Universal Voltage 120V – 277V, 1%-100% dimming on 0-10V controls at 277V, 1%-100% dimming on LE/TE phase-control dimmers at 120V

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 28.4 W | CRI | 100 |
| Total flux | 2262 lm | LOR | 100% |
| Luminous efficacy | 80 lm/W | Total power | 28.4 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.39 in
Diameter: 2.00 in

### Adjustability

Fixed

### Electric

System power: 28.4 W

### Protection

IP: 47