Product data sheet

FLEX50
FX50E-949301-HXXXO
EGLO



recessed mounted direct LED luminaire;

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	90
Total flux	416 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	4.4 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 77.83 in
Width: 72.01 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 39.6 W

Protection

IP: 20
Designation labels: CE