Product data sheet

LED DIMMABLE SQUARE SURFACE PANEL 6W 2800K SSPL-6V/DIM


MPE





- Square shape - Surface - mounted on ceiling - Light frame made of anti-oxidation aluminum alloy - Light guide plate made of PMMA plastic for uniform light distribution - Detachable driver for easy connection, Integrated driver EMC. - Use with Dimmer LED to adjust brightness - Size: 120 x 120 x 35 mm - Voltage: 100-240VAC - Power: 6W - Power Factor (PF): >0.5 - Luminance: 500 lm - Color Temperature (CCT): 2800-3200K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

Light output 1



1 x LED	
Nominal lamp power	6 W
Lamp flux	500 lm
Luminous efficacy	82 lm/W
CCT	2800 K
CRI	81

LOR	98%
Total flux	492 lm
Total power	6 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.72 in Width: 4.72 in Height: 1.26 in Weight: 20.819 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 6 W

Protection

IP: 20