



Product data sheet

MIC 3 CLUSTER COLUMN PROJECTORS
MI-21052-M-W40-A50231
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000, > 50,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear tempered glass - Integral control gear installed in the pole top

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Light output 3 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Light output 4 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Light output 5 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Light output 6 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.2 W	CRI	80
Total flux	3614 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	37.2 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 216.54 in

Diameter: 7.76 in

Weight: 49.8 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 223.2 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 07

Surface temperature: 40°C