Product data sheet

SRT-SYSTEM IP20-SRGODA/1500 LED - GERÄTETRÄGER FIX INDIVIDUAL.LENS.OPTIC | DEVICE MOUNT FIX INDIVIDUAL.L.. 8000-4000 830 7697LM ETM SG RAL 9006 (SRT+19460004235)


REGIOLUX



IP 20 IK 03

SRT-Quick-fit mounting system, Device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Housing colour silver grey/white aluminium RAL 9006. Light distribution direct double asymmetrical distribution by means of Individual.Lens.Optic of PMMA plastic, the single lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 3-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. The device mount can be adjusted variably in steps with a multi-lumen driver. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Additional information on the driver switching stages is available on the Internet on the product details page or in the product data sheet under the heading Operating Data. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 70°(C0)/90° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 3000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 35°C) Nominal luminous flux/switching steps (rounded): 7700lm/53W, 6700lm/45W, 5700lm/37W, 4100lm/26W (Standard setting 7697lm) Luminaire luminous efficiency: 160lm/W-145lm/W Control gear: Electronic multi-lumen driver, 4-steps (1 pcs.) System output: 53W-26W Energy efficiency class/light source: D Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 35°C) Ambient temperatur: ta -20°C to 35°C UGR lat./long.: 20.1 / 18.8 (53W) Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGODA /1500 LED 8000-4000 830 ETM sg RAL 9006 Article number: 19460004235 Product deep link: https://www.regiolux.de/en/article/19460004235 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	53.1 W	CRI	80
Total flux	7697 lm	LOR	100%
Luminous efficacy	145 lm/W	Total power	53.1 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 53.1 W
Appliance Class: 0

Design

Color of housing: Silver gray

Protection

IP: 20

IK: 03

Designation labels: CE, ENEC