

# Product data sheet

FLAT POLYMERO  
311627.002.2  
RZB



IP  
40

IK  
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 100 Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1550lm System power: 19W Beam Angle: 119° Number of fittings B10A: 30 Number of fittings B16A: 50 Inrush current: 16A Unified Glare Ratio: 20,9 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	19 W	CRI	80
Total flux	1550 lm	LOR	100%
Luminous efficacy	82 lm/W	ULOR	12%
		Total power	19 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 11.81 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 40  
IK: 10