Product data sheet


MARVEL 3 LIGHT COLUMNS
MAV-20005-C-8030
LIGMAN



IP 67 IK 07

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing - Extruded aluminium column - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34.4 W	CRI	80
Total flux	3155 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	100%
		Total power	34.4 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 98.43 in
Diameter: 11.81 in
Weight: 8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 34.4 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 07
Surface temperature: 40°C