


Product data sheet

JET 53 WALL LUMINAIRES
JE-30383-E-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Two cable entries for through wiring for JE-30393, JE-30413, JE-30383, JE-30403 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	18.2 W	CRI	80
Total flux	920 lm	LOR	100%
Luminous efficacy	51 lm/W	ULOR	50%
		Total power	18.2 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	18.4 W	CRI	-50
Total flux	133 lm	LOR	100%
Luminous efficacy	7 lm/W	ULOR	50%
		Total power	18.4 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	18.4 W	CRI	-18
Total flux	912 lm	LOR	100%
Luminous efficacy	50 lm/W	ULOR	50%
		Total power	18.4 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	13.6 W	CRI	-29
Total flux	502 lm	LOR	100%
Luminous efficacy	37 lm/W	ULOR	50%
		Total power	13.6 W

Mounting mode

Wall mounted

Shape and measurements

Height: 10.31 in
Diameter: 6.30 in
Weight: 5.3 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 68.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C