



Product data sheet

TRACK SPOTLIGHT MATRIX PRO CRI > 90 3000K 22W ON/OFF BLACK (F)
2000.8783 - MATRIX LED2750-930 40 BK PRO ONF
REGENT



Track spotlight Matrix with conductor track adaptor for three circuit track Global Trac Pro, with LED, colour rendering index CRI > 90, colour temperature 3000 K, warm white, system power: 22 W, luminous flux of luminaire 2750 lm, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, 1 integral control gear, ON/OFF, control gear box in die-cast aluminium, reflector housing in die-cast aluminium, black, similar to RAL 9005, wide beam, (F), 40°, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0310), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class E Ø = 127 mm, L = 175 mm, B = 92 mm, A = 210 mm, pivotable 360°, swivelling 45°

Light output 1



1 x LED			
Nominal lamp power	22 W	LOR	100%
Lamp flux	2750 lm	ULOR	10%
Luminous efficacy	125 lm/W	Total flux	2750 lm
CCT	3000 K	Total power	22 W
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 7.05 in
Width: 12.40 in
Height: 7.99 in
Weight: 1.983 kg

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black

Electric

System power: 22 W
Appliance Class: I

Protection

IP: 20