Product data sheet


2567 PODIO - DIP SWITCH 4000K CRI 80 25W CLD
422540-00
DISANO



IP 66 IK 08

Housing: die-cast aluminium, with central die-cast aluminium joint. Optics: in high-performance silver-coated aluminium. Diffuser: extra-clear, tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI-EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: with surge protection in compliance with EN 61547 to protect the LED module and the related ballast. On request: 1/10 DIMM or DALI versions.

Light output 1



1 x LED

Nominal lamp power	25 W	LOR	100%
Lamp flux	3493 lm	Total flux	3493 lm
Luminous efficacy	140 lm/W	Total power	25 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.88 in
Width: 4.88 in
Height: 6.14 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE