


Product data sheet


SINUS SUSP. DI/ID SILVER PRISM. 1174MM
R33H117-9006E2940H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP
40


high output LED 4000K CRI 90 159,5W 19096lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogeneity. The light distribution is thus influenced and the luminous flux is reduced by 13,2% <https://katalog.planlicht.com/en-gb/fam-sinus/>]

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.94 W	CRI	90
Total flux	2387 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	19.94 W

Mounting mode

Pendant

Shape and measurements

Length: 46.22 in

Width: 46.22 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 159.5 W

Protection

IP: 40