


Product data sheet

LIGHTTALK 4 PENDANT LUMINAIRES
LA-95021-VN-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° C 135,000, 300,000 - Life time L80B10 Ta 50° C 310,000, > 500,000 - Die-cast aluminium end-caps and extruded aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Stainless steel suspension kit in grade 304 - Suspension height is fully adjustable - Durable silicone rubber gasket - Clear toughened glass - Integral control gear for LA-95001, LA-95002 - Remote driver is included for LA-95021, LA-95022

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 28.7 W | CRI | 80 |
| Total flux | 2594 lm | LOR | 100% |
| Luminous efficacy | 90 lm/W | Total power | 28.7 W |

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 23.86 in
Width: 2.56 in
Height: 47.24 in
Weight: 2.1 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 28.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 10
Surface temperature: 40°C