

Product data sheet

MINITWIST


S.3018N

SIMES



Version is available on request. SPOTLIGHTS MINI-TWIST FLOOD S.3018N 1 module COB 4000K 220-230Vac DIMMABLE DALI; DALI2; PUSH
Rated module luminous flux: 2556lm Rated luminaire luminous flux: 1679lm Rated module power: 15.3W Rated luminaire power: 17.8W
Luminaire efficacy: 94lm/W Voltage (AC): 220-230Vac Frequency (AC): 50/60Hz Voltage (DC): 198-276Vdc (No PUSH DIM) Dimmable: DALI; DALI2; PUSH PUSH Synchronization: - Max 4 Luminaires, distance <15m; - Max 35 Luminaires, distance <300m with S.2490 accessory.
Electrical insulation class: I Protection class IP: IP65 Mechanical resistance: IK09 CE ENEC SPECIAL VERSION ON REQUEST: this
Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at
460mA $V_{min}=31.2Vdc$ $V_{max}=36.8Vdc$. Example SIMES compatible power supplies (check the complete list of the drivers on the catalogue):
Art. S.2438 POWER SUPPLY 230V/250mA-700mA 20W o 230Vac/24Vdc 16W 240Hz DALI DIMMABLE IN BOX IP67 Art. S.3426 POWER
SUPPLY DALI MULTI-POWER 230V/250mA-700mA o 230V/24V 16W 240Hz IP20 NB: Use 1 Power Supply for each Luminaires LUMINAIRE
TYPE Projector. IP rating IP 65 MATERIAL CHARACTERISTICS Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
Extruded EN AW-6060 aluminium structure (arm version) with high corrosion resistance. Stone wash surface treatment prior to painting
process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Silicone gaskets.
Painting Process : 3 Step Process 1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic
nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy
primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3)
POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions.
Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 09 LIGHTING PERFORMANCE Reflector in 99.98% pure
anodized aluminium HI-GRADE (version with LED COB). Clear toughened glass. LOR – INSTALLATION AND MAINTENANCE The tempered
front glass diffuser is fixed externally to the fitting through silicon resin, perfectly flush with the front ring. Water and dirt deposits that can
disturb the lighting performance of the projector can easily flow away. The pre-wired connecting wall plaquette and its fast connector make
the installation and maintenance process quick, easy and safe. WIRING Supplied with a 6,0m pre-wired H05RNF cable and fast connector .
Isolation: CLASS I . Available colours: Aluminium grey (cod.14), White (cod.01). Weight: 3.13 Kg Glow Wire test: -- LED module included TWIST
PATENTED, REGISTERED DESIGN This luminaire contains built-in LED modules. In case of damage or malfunction please contact the
manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the
luminaire by the end user. This product contains a light source of energy efficiency class: E. LED modules are engineered accordingly to the
existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000
hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 50,000 hours at 40°C.
Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -
20°C to +60°C. ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE. We recommend installing surge protection devices ?SPD? in the
electrical system. Protection devices prevent the intensity of these phenomena?s, protecting the appliances from the risk of being damaged
and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such
disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by
SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection
device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the
electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type	LED	CCT	3800 K
Nominal lamp power	17.8 W	CRI	86
Total flux	1679 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	17.8 W

Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

Shape and measurements

Length: 1.83 in
Width: 1.69 in
Height: 3.89 in

Adjustability

Rotatable

Design

Color of housing: White

Electric

System power: 17.8 W
Appliance Class: I

Protection

IP: 65
IK: 09
Designation labels: CE, ENEC