Product data sheet


NLED5822B（KA专供）2×9W 24°3500K 双头通用型格栅射灯（工程专供）
70075648
NVC



IP 20 IK 04


产品描述： 光源类型：优质COB芯片 驱动电源：外置隔离式恒流驱动 灯体材质：铝合金 面环颜色：半光白 安装方式：嵌入式 投射调节：可调节（水平MAX ±355°，垂直MAX ＋30°）系列可选 ： 防眩筒外观：KA专供/KA细筋/KA粗筋 单灯头数 ：单头/双头/三头 光通（lm）：370/380/400/400（1×6W）； 470/480/500/500（1×9W）； 700/720/750/750（1×12W）； 1070/1100/1150/1150（1×20W）。 光束（°）：15/24 色温（K）：3000/3500/4000/5700 显指（Ra）：80 功率（W）：1×6/2×6/3×6（NLED582*A）；1×9/2×9/3×9（NLED582*B）； 1×12/2×12/3×12（NLED582*C）； 1×20/2×20/3×20（NLED582*D）。 功率因数PF：0.80（NLED582*A）；0.90（NLED582*B、NLED582*C、NLED582*D）。 更新说明： 暂无更新，敬请期待。 更多信息： 暂无链接，敬请期待。

Light output 1 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	9 W	CRI	80
Total flux	480 lm	LOR	100%
Luminous efficacy	53 lm/W	Total power	9 W

Light output 2 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	9 W	CRI	80
Total flux	480 lm	LOR	100%
Luminous efficacy	53 lm/W	Total power	9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.17 in
Width: 5.14 in
Height: 3.27 in

Electric

System power: 18 W
Appliance Class: II

Protection

IP: 20
IK: 04

Adjustability

Rotatable, Free