Product data sheet


PLANADO RZ
672617.002.07
RZB



IP 54 IK 05


Series: PLANADO Attractive escape sign luminaire. Housing and end caps made of sheet steel, powder coated. End caps with hidden screws, with permanently dimensionally stable silicone foam seal. Rectangular diffuser made of non-yellowing plastic (PMMA), opal. Suitable for Wall (surface). Self-contained system with automatic self-test and feedback via DALI bus, only to RZB DALI monitoring system. 4 legends for escape route identification included. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments in which a deposit of non-conductive dust on the luminaire can be expected. Colour: white Length: 320 mm Width: 160 mm Height: 59 mm Weight: 1.5 kg Operating mode: maintained power mode Viewing Distance: 30 m Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 3.1 W Rated luminous flux: 130 lm Luminous flux, emergency: 60 lm System power, emergency: - Control gear: Regulated power supply Protection class: I Type of protection: IP 54

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.1 W	CRI	80
Total flux	130 lm	LOR	100%
Luminous efficacy	42 lm/W	ULOR	15%
		Total power	3.1 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.1 W	CRI	80
Total flux	60 lm	LOR	100%
Luminous efficacy	19 lm/W	ULOR	15%
		Total power	3.1 W

Mounting mode

Wall mounted

Shape and measurements

Length: 6.30 in
Width: 12.60 in
Height: 2.32 in

Electric

System power: 6.2 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 54

IK: 05