



Product data sheet

COMFORT LED 900 TW 29W 2700-6500K RA>80 FREEBLUE
8246092272
SG ARMATUREN



Comfort LED TW wall uplight is highly suitable for indirect lighting in corridors, as well as general additional accent lighting in offices and meeting rooms. The luminaire creates an indirect glare-free lighting using the wall and ceiling surface. Tunable White from 2700 Kelvin to 6500 Kelvin white light. Controlled by Dali Type 8. Comfortable indirect glare-free lighting Good addition to the ceiling lights Suitable for corridors Light distribution Indirect asymmetric Light source LED (2700-6500K): Max 29W Ra>80 SDCM: 3 Optics White painted reflector Materials and finish Housing: Sheet steel, powder coated white. Clear cover glass covering the LED's is easy to wipe/clean. Control gear DALI Type 8 FreeBlue Protection Class I, IP20, Ta=25°C, CE. Mounting/Connection Surface mounted. Direct on wall. Cable entry through holes in back of the luminaire.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3070 lm	LOR	100%
Luminous efficacy	106 lm/W	ULOR	100%
		Total power	29 W

Mounting mode

Wall mounted

Shape and measurements

Length: 35.24 in

Width: 5.68 in

Height: 1.76 in

Adjustability

Fixed

Electric

System power: 29 W

Color adjustable

Appliance Class: I

Protection

IP: 20