
Product data sheet


SINUS RECESSED FRAME SILVER SAT. 1926MM
R33E192-9006E1HCLX3S
PLANLICHT



IP 40


dynamic white LED 2700-6500K CRI 90 136,6W 14436lm DALI DT8 https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	17.08 W	CRI	90
Total flux	1805 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	17.08 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 75.83 in
Width: 75.83 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 136.6 W
Color adjustable

Protection

IP: 40