



Product data sheet

SANDY 1 SURFACE MOUNTER LUMINAIRES
SA-31471-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal, impact-resistant, UV-stabilised polycarbonate diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	19.7 W	CRI	80
Total flux	579 lm	LOR	100%
Luminous efficacy	29 lm/W	ULOR	50%
		Total power	19.7 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.13 in
Diameter: 8.11 in
Weight: 2.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 19.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C