Product data sheet


GRIP! PD, PHASE, Ø 3.0CM
1008466
SLV



IP 20 IK 02


GRIP! - the striking light family for sophisticated lighting design. With its distinctive knurled front ring and many new pendant, surface-mounted and recessed options, GRIP! now offers even more options for customised lighting concepts. The honeycomb louvre insert supplied as standard reduces glare and ensures optimum visual comfort. Different colours and designs blend harmoniously into living spaces, hotels or restaurants. High-quality technology with a CRI of 90, a lifetime of 50,000 hours and easy installation make GRIP! an all-round convincing choice.

Light output 1




1 x LED

Nominal lamp power	10.8 W	LOR	100%
Lamp flux	650 lm	Total flux	650 lm
Luminous efficacy	60 lm/W	Total power	10.8 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	10.8 W	LOR	100%
Lamp flux	580 lm	Total flux	580 lm
Luminous efficacy	54 lm/W	Total power	10.8 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	10.8 W	LOR	100%
Lamp flux	310 lm	Total flux	310 lm
Luminous efficacy	29 lm/W	Total power	10.8 W
CCT	2000 K		
CRI	90		

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 1.18 in
Width: 1.18 in
Height: 12.05 in
Weight: 0.29 kg

Adjustability

Height adjustable

Electric

System power: 10.8 W
Controller: DALI

Protection

IP: 20
IK: 02