

Product data sheet


KTRIBE F1 CRO/ALL.BRO.
F6265046
FLOS



IP
20

Floor lamp providing diffused lighting; a switch located near the diffuser allows for 4-level light adjustment via a “remote” dimmer positioned on the power cord near the plug. Base and rod support in die-cast, polished Zamak alloy. Rod, arm support, arm and diffuser support in polished aluminum tube. Molded steel counterweight with galvanized finish. Injection-molded PC (polycarbonate) inner diffuser opal color. Outer diffusers in plissé cloth, transparent PMMA (polymethylmethacrylate), silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent, or transparent brown for the outer bronze diffuser. FEP/PVC, UV-stabilized transparent power cord length 1500 mm. Net weight 4,3 kg.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	70 W	Socket	E27
Lamp flux	1240 lm	LOR	15%
Luminous efficacy	3 lm/W	ULOR	7%
CCT	2800 K	Total flux	183 lm
CRI	99	Total power	70 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 9.84 in
Width: 9.84 in
Height: 34.45 in

Adjustability

Rotatable

Electric

System power: 70 W

Protection

IP: 20