Product data sheet

DVO15-38-044 VCF EM3 MT 840

ASTZ



ДВО15-38-044 VCF EM3 MT 840 ТУ 3461-063-05014337-2016 Предназначены для общего освещения административно общественных помещений и производственных зданий, “чистых” комнат. 220 В, 50 Гц, 36 Вт, 4000К, Ra=80, драйвер (PF= 0,95), IP54, УХЛ4 Световой поток светильника: 4398 лм Класс защиты от поражения электрическим током: I LxBxH=600x600x65 мм. Масса: 6,3 кг Корпус - листовая сталь, окрашен белой порошковой краской (сварной). Рассеиватель из защитного закалённого матированного стекла. БАП рассчитан на работу в аварийном режиме в течение 3х часов, магнитный тестовый выключатель БАП. Установка в подвесные потолочные системы Armstrong: потолки V-Clip F на пружинную Т-рейку BPC1801H и Clip-in (Q-Clip, R-Clip, S-Clip) на рейку BT-600, а также в потолки Albes AC на рейку BT-600.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35.8 W	CRI	80
Total flux	4398 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	35.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.56 in

Adjustability

Fixed

Electric

System power: 35.8 W

Appliance Class: I

Protection

IP: 54