# Product data sheet

PRO L120 PROSPORT LED

**DEXTRA** 










ProSport LED - 1000mm, IP40, IK10 Sports luminaire with white steel housing and curved clear polycarbonate diffusers. Supplied with trunking bracket mounting spine and two suspension wire toggles. Can be surface mounted, trunking mounted or suspended. Options: E3 - Emergency control gear (684 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) AS - Asymmetric 20° Bracket (rigid mounting only) PRO 5M Suspension - 5 metre suspension kit (not suitable where ball strikes may occur)

#### Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	63.7 W	CRI	80
Total flux	9504 lm	LOR	100%
Luminous efficacy	149 lm/W	Total power	63.7 W

# Mounting mode

Ceiling mounted, Pendant

### Shape and measurements

Length: 40.94 in Width: 16.06 in Height: 4.53 in

# Adjustability

Fixed, Height adjustable, Free

#### Electric

System power: 63.7 W

Ballast: ECG

#### Protection

IP: 20 IK: 10

Resistant to impact of balls Designation labels: CE