

# Product data sheet

LD59 1.6W 500MA WWB


LD59-C1-500-WWB

LIGHTGRAPHIX



LD59 90mm x 90mm Recessed Wall Light. Constant Current. 1.6W 500mA 120° Wide beam. LD59 replaces the LD10234 and offers the same low glare and broad illumination with an IP67 rating for both interior and exterior projects. The square recessed wall light uses a single LED for a soft edge beam with no multiple shadows. It comes as standard with a 1.5mm polished & passivated 316 stainless steel bezel with no visible fixings. The specular reflector gives a diffused wash of light onto a path or floor with minimal glare.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.6 W	CRI	93
Total flux	101 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	1.6 W

## Mounting mode

Wall recessed

## Shape and measurements

Length: 1.50 in

Width: 3.54 in

Height: 3.54 in

## Adjustability

Fixed

## Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel

Color of housing: Black, White, Anthracite / graphite, Silver gray

## Electric

System power: 1.6 W

Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI

Appliance Class: III

## Protection

IP: 65

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F