Product data sheet

PAULA VIII 9.648.3046.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	50 W	
Lamp flux	2000 lm	
Luminous efficacy	28 lm/W	
CCT	3400 K	
CRI	54	

LOR	83%
Total flux	1662 lm
Total power	59 W



Mounting mode

Diameter: 28.74 in

1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	
Lamp flux	4000 lm	Total flux	
Luminous efficacy	37 lm/W	Total power	
CCT	3400 K		
CRI	54		

Electric

Pole top mounted System power: 59-89 W

Shape and measurements Protection

Height: 28.74 in IP: 55

83%

89 W

3324 lm