


Product data sheet

PROFILE AREA 100 DOWN
P21XBD40X04 - 38W 4000K 1.2M, 120-277V DRIVER
FLUXWERX ILLUMINATION



Profile is a high performance indoor, linear suspended luminaire with a signature architectural form and luminous open interior. Its anidolic optical system supports a multitude of applications via 5 distributions from 100 Down to 65 Up | 35 Down, as well as asymmetric wall wash and independently controlled hemispheres. This also allows wider spacing – up to 3.5m on centre – and fewer luminaires. Available in discrete 1.2m (4ft), 1.8m (6ft) or 2.4m (8ft) lengths, as well as continuous rows, completed by a choice of 5 endcap styles – Angle, Bevel, Flat, Capsule or Square.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	37 W	CRI	80
Total flux	3941 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	75%
		Total power	37 W

Mounting mode

Pendant

Shape and measurements

Length: 49.00 in
Width: 2.36 in
Height: 2.53 in

Adjustability

Height adjustable

Design

Color of housing: Black, White, Silver gray

Electric

System power: 37 W

Protection

IP: 20
Designation labels: CE, UL