
# Product data sheet

FLEXBLEND, SUSPENDED SP341P LED26S/940 MLO EL3 L1500
SP340P
PHILIPS



FlexBlend heading the way to efficient and flexible furnished offices areas Philips FlexBlend is an attractive family of surface mounted and suspended luminaires, next to Flexblend recessed. The luminaire range is enabling building owners to advance their lighting operations, by offering office-compliant lighting with a return on investment of less than 3 to 4 years. FlexBlend provides the required flexibility through the adaptability in design. This gives the possibility to install the luminaires easily in the field, at any moment. Even when todays luminaire is suspended, tomorrow this can be adapted to a surface mounted installation at the venue. And the other way around. The surface mounted and suspended luminaire range fit to many different office spaces like open plan office, corridors, reception or meeting rooms. FlexBlend is offered in both lines and as standalone, using the same lighting module. This gives the option to the users to use FlexBlend as standalone now, and tomorrow, as line. The controller is integrated in the luminaire. As technology is changing fast, the ideal lighting solution is also expected to be ready to incorporate innovations that can help optimize operations further. For this reason, FlexBlend holds all connectivity and future ready options available. As System Ready luminaire it can be paired with lighting management systems such as the Philips SpaceWise, and to software-based lighting systems as Interact Office wired (PoE) and Interact Office wireless and/or existing and upcoming sensor innovations. The luminaire range is therefore future ready and can be delivered without any system component, and in a next phase, in the field to be upgraded. An attractive opportunity for new installations and renovations.

## Light output 1



### 1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 4 W | LOR | 100% |
| Lamp flux | 2600 lm | Total flux | 2589 lm |
| Luminous efficacy | 647 lm/W | Total power | 4 W |
| CCT | 4000 K | | |
| CRI | 90 | | |

## Mounting mode

Pendant

## Electric

System power: 4 W

## Shape and measurements

Length: 57.87 in
Width: 7.87 in
Height: 8.90 in